

BUTYL TUBES & FLAPS



FEATURES

- High Quality Butyl Rubber
- Exceptional Air Retention
- Preferred Fitment in Radial Tyres
- Good and Strong Splicing
- 100% Defect-free Tube
- High Quality Valves

PRODUCT SEGMENT

- Two & Three Wheeler
- Passenger Car - Conventional & Radial
- Light & Heavy Commercial Vehicle
- Tractor, Forklift & Industrial Vehicle
- Off-The-Road Vehicle (OTR)
- Animal Driven Vehicle (ADV)

TECHNICAL SPECIFICATION

TYPE	TUBE SIZE	VALVE	TYPE	TUBE SIZE	VALVE
TWO WHEELER	2.25/2.50-16	TR29	TRACTOR	10.5-18	TR218A
	2.75/3.00-10	V1.08.1		12.5-18	TR218A
	3.50-10	V1.08.1		12.4-24	TR218A
	2.75/3.00-14	TR29		14.00-24	TR218A
	2.75/3.00-16	TR29		11.2 / 12.4-28	TR218A
	3.25/3.50-16	TR29		13/14.9-28	TR218A
	2.25/2.50-17	TR29	OTR	14.00-20	TR179A
	2.75/3.00-17	TR29		11.00/12.00-24	TR78A / V3.02.14 / V3.04.5
	100/90-17	TR29		12.00/13.00-24	TR78A / V3.02.14 / V3.04.5
	100/90-18	TR29			
	2.50/2.75-18	TR29			
	2.75/3.00-18	TR29			
	3.50-18	TR29			
	3.25/3.50-19	TR29			
THREE WHEELER	3.50-8	V1.08.3	ADV	6.00-19	TR14, TR 15
	4.00-8	V1.08.3		7.00-19	TR 14, TR 15
	4.50-10	TR 13	9.00-16 / 12x16-5	TR75A / TR76A / TR177A	
PASSENGER CAR / TRUCK	4.00 / 4.50-12	TR13	FORKLIFT / INDUSTRIAL VEHICLE	5.00-8	JS2
	5.00 / 6.00-12	TR13		18x7-8	JS2
	6.00-14	TR13		16x6-8	JS2
	H78-15 / L78-15	TR13 / TR15		6.00-9	JS2 / TR274A
	6.50-15	TR 13		21x8-9	JS2
	5.50/6.00-16	TR15 / TR13		6.50-10	JS2 / TR 274 A
	6.00/6.50-16	TR15 / TR75A		23x9-10	JS2 / TR15 / TR75A
	135/145/155-12	TR13		6.00-12	TR13
	8.15-15	TR 76A, TR 75A		7.00-12	TR75A / JS2
	135/145/155-13	TR13		7.00-15	AB 1582
	155/165/560-13	TR13		23x10-12	TR75A
	175/185/650-13	TR13		27x10-12	TR75A
	175/185/195/650-14	TR13		28x9-15	TR75A
	195/205/215/225-15	TR13		250-15	TR75A
LCV	7.00/7.50/8.15/7.00R15	TR75A / TR76A	FLAPS	3.50 / 4.00 / 5.00 / 5.70-8 / 18x7-8	
	8.25-15	TR177A / TR13		6.00 / 6.90 -9 / 21x8-9	
	7.00-16	TR15 / TR75A		23x9-10, 6.50 / 7.50 - 10	
	7.50-16 / 7.50R-16	TR15 / TR75A		6.50 / 7.00 / 8.25 - 12, 23x10-12 / 27x10-12	
	8.25-16	TR75A / TR76A		6.50 / 7.00 / 7.50 -15, 8.15 / 8.25 / 9.00-15	
HCV	7.50-20	TR175A / TR177A		250 / 300-15, 7.00 / 7.50 / 9.00 -16, 7.50 / 8.25 - 20	
	7.50/8.25-20	TR175A / TR177A		9.00 / 10.00 -20	
	9.00-20 R	TR175A		11.00 / 12.00 - 20	
	10.00-20	TR78A		10.00 / 11.00 / 12.00 - 22	
	11.00-20 R	TR78A		11.00 / 12.00 / 13.00 - 24	
	12.00-20 / 12.00R-20	TR78A		13.00 / 14.00 -24/25, 16.00 / 24/25	
	8.25-20 R	TR78A	18.00 - 24/25		



EMERALD RESILIENT TYRE MANUFACTURERS PVT. LTD.
 PLOT NO.2, 2ND STREET, PHASE 1
 PORUR GARDEN, VANAGARAM
 CHENNAI 600 095, INDIA
E-MAIL enquiry@emraldtyres.com
TEL +91 44 6646 0555 / 0566
FAX +91 44 6646 0550

EMERALD MIDDLE EAST FZE
 P.O BOX 86009, RAKIA FREE ZONE
 RAS AL KHAIMAH, U.A.E.
E-MAIL info@emraldmiddleeast.com
TEL +971 7 2433195
FAX +971 7 2433189

EMERALD TYRES EUROPE B.V.B.A.
 PATHOEKEWEG 130 C
 8000 BRUGGE, BELGIUM
E-MAIL info@emraldtyres.com
TEL +32 50310900

